

Sealer Non-drop

Product properties

Alkali resistant transparent blue-tinted primer with good penetration. Provides effective base and adhesive surface on mildly chalking and absorbent substrates. Used before painting or installation of wall covering.

- Primer agent
- Transparent
- Matt



Labelling



Product use

Plaster, concrete, cardboard-coated gypsum board and filled surfaces before installing wall coverings or painting with ceiling and wall paint.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.

Water-soluble discolouration, nicotine and soot can be cleaned with Fluren 49.

Sand surface to matt finish as required.

Cracks, unevenness and holes must be filled.

Application

Brush, roller or spray.

Adjust the choice of tool, when spraying, adjust pressure and nozzle selection.

After spray application, it is recommended to process the substrate "wet-on-wet" with a brush or roller.

Cold/heat can affect the viscosity of the material.

Material temperature for spray painting, min. 12°C.

Condensation during drying/curing must not occur.

Cold and increased humidity extends drying time, full curing and recoat interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Uniformly saturated and transparent surface.
The surface must not appear glossy after application.
Finished with wall covering and/or paint in desired gloss and colour.

Please note!

Where old wallpaper or wall coverings are being removed and new installed, priming using stabilising agents together with glue residue can lead to over priming.
Instead, use Flügger Combi Primer.
In the event of over priming, curing time is lengthened along with the risk of poor adhesion.

Environmental information

Clean off the paint from tools and wash them with water. Bring remains of fluent paint to the local recycling centre.
Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost-free, and tightly closed

Supplementary Info

Registered in the Nordic Ecolabelling Building Products Database for products which can be used in buildings with the Swan label.

For this product there is issued an: [Environmental Product Declaration](#)

Technical Data

Product Type	Primer
Density (kgs/l)	1.03
Solids Weight %	13
Solids Vol. %	11
Nominal spreading rate (m ² /ltr.)	5
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	3
Fully cured at 20° C, 60 % RH (Days)	28
Emission acc. to ISO 16000-9:2011 (< µg/m ² h after 28 days)	10
Dilution	Do not dilute
Cleaning of Tools etc.	Water

Current TDS Version

October 2023

Replaces TDS Version

September 2023

