

Natural Wood Beewax

Product properties

Care product based on pure beeswax and non-volatile oils that make the beeswax easy to work with. Gives the wood a classic, beautiful, antique golden glow that prevents the wood from drying out and makes the surface dirt-repellent and easy to clean.

- Dirt-repellent surface
- Golden glow
- Prevents drying out



Labelling



Product use

Used for indoor woodwork, especially waxing of furniture.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Dirt, grime and grease are removed with Natural Wood Cleaner.

Application

Shake before use.

Apply with a clean, dry cloth.

After 15-20 minutes, buff with a dry cloth.

Always perform a test treatment for control and acceptance of the result.

Expected result

Dirt-repellent and easy to clean surface.

Cleaning and maintenance

Regular cleaning/maintenance can be carried out with Natural Wood Cleaner.

Re-treatment with beewax is recommended 1-2 times a year.

Please note!

Rags containing the product may spontaneously combust.

Saturate with water or destroy.

Environmental information

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Impregnation
Density (kgs/l)	0.92
Nominal spreading rate (m ² /ltr.)	25
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Cleaning of Tools etc.	Water and soap
Country of Origin	Denmark

Current TDS Version

December 2024

Replaces TDS Version

April 2024