

# Ding-dong

## Properties

Type: Acrylic lacquer, semi-matt. Ding-dong is an acrylic lacquer ready for stirring in of vinyl chips. A semi-matt surface is obtained, which is very robust against mechanical wear and cleaning. The chips effect blurs an imperfect ground, but the chips may cause a minor roughness, which can be reduced by slight sanding and extra application of Ding-dong lacquer.



## Use

Suitable interior for walls in staircases, corridors, hobby rooms etc., where a robust surface is required.

The surface must be clean, dry and solid, and it must be uniformly painted with e.g. Flutex 5, matt latex paint.

To 2 1/2 litres of lacquer add 100 g chips, and to 10 litres of lacquer add 4 x 100 g chips, possibly several different colours depending on the required effect.

The vinyl chips are preferably stirred in with a mixer for approx. 5 minutes.

The ready-mixed Ding-dong should be applied within 24 hours.

Application by brush or roller. Maximum layer 180 µ in order to prevent the lacquer to appear yellow.

NB: Secure a warm and effective ventilation during application. Low temperature/high humidity can result in yellowing of the film.

**Storage:** Cool, frost-free and tightly closed

## Technical Data

Product Type	Laquer
Gloss	20;Semi Matte
Density (kgs/l)	1,03
Solids Weight %	21
Solids Vol. %	18
Nominal spreading rate (m <sup>2</sup> /ltr.)	6
Min. working temp. during application and drying/curing	Min. +5°C
Drying time at 20° C, 60 % RH (Hours)	2
Recoatable at 20° C, 60 % RH (Hours)	12
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Normally not to be diluted
Cleaning of Tools etc.	Water

### Current TDS Version

January 2019

