

# Facade Anti-green

## Properties

Concentrated cleaning agent for removal of fouling on all external surfaces.

- Efficient removal of fouling

## Use

For exterior use on facades, masonry, woodwork, roof tiles, glass, plastic, etc.

To be used at +5 °C. Please notice that if the product is used at e.g. +20 °C the efficiency will increase and the waiting time will shorten correspondingly.



## Application

Cleaning before painting

Remove dirt and impurities with Flügger Facade Clean. Follow the instructions indicated on the packaging. Then apply Flügger Facade Anti-green and let dry.

The surface is now ready to be painted.

Cleaning without subsequent painting

Apply by low-pressure sprayer, paint brush or brush until saturation of the substrate is achieved. After 1-4 days, depending on the degree of the growth, remove the residues with a stiff brush and water.

If the substrate withstands cleaning with a high-pressure cleaner, you can also remove the residues this way.

Preventing cleaning

Flügger Façade Anti-green is very suitable as preventive protection against fouling. Apply and let dry without washing off.

## Environmental information

Remove the cap before recycling

**Storage:** Cool, frost-free and tightly closed

## Technical Data

Product Type	Cleaning
Dosing	1:4
Nominal spreading rate (m <sup>2</sup> /ltr.)	6
Cleaning of Tools etc.	Water

**Current TDS Version**

December 2021

**Replaces TDS Version**

June 2020