

# Facade Anti-green, spray

Flügger Facade products are used for exterior surface treatment and maintenance.

## Product properties

Algae and mould remover spray that removes fouling on all outdoor surfaces.

- Effectively removes fouling
- Cleans and freshens
- Long lasting



## Product use

Used outdoors on: facades, walls, stone, wood, plastic, roofs, etc.

## Substrate

Surfaces must be clean, dry, solid and suitable for treatment.

## Treatment

Can be used at temperatures as low as +5 °C, but is 3-4 times more efficient at +20 °C and has a shorter drying time.

## Application

Painted facade, repainting:

Apply the spray, allow to stand for 48 hours, depending on the degree of fouling and temperature. Then wash the surfaces using Facade Clean.

Painted facade, without repainting:

Apply the spray, allow to stand for 48 hours, depending on the degree of fouling and temperature. Clean using Facade Clean. Alternatively, apply the spray and let the weather take care of the rest.

May be slightly corrosive to aluminium, zinc, copper and other porous metals. Protect sensitive vegetation or moisten with water before treatment.

## Good practise

Check facades regularly and remove fouling immediately.

## Expected result

Clean surface ready for paint treatment, if desired.

## Cleaning and maintenance

Flügger Facade Anti-green Spray offers ideal preventive protection against contamination. Apply and allow to dry without rinsing off.

## Please note!

Do not apply near or above surface water, such as lakes or streams.

## Environmental information

Remove the cap before sorting the packaging for recycling.

**Storage:** Cool, frost-free and tightly closed

## Technical Data

Product Type	Cleaning
Mixing ratio	Ready-to-use
Nominal spreading rate (m <sup>2</sup> /ltr.)	5
Min. working temp. during application and drying/curing	Min. +5°C
Cleaning of Tools etc.	Water

### Current TDS Version

March 2023

### Replaces TDS Version

December 2021