

# Adhesive 290 Wallpaper

Fiona Adhesive is adhesive for hanging wall coverings.

## Properties

Ready-mixed, transparent, reinforced adhesive. For hanging non-woven wallpapers where the adhesive is applied to the wall.



- Wallpaper adhesive, non-woven
- Easy to apply
- Can be sprayed on

## Labelling



---

Name: 12 L



---

Name: 5 L



---

Name: 0,75 L



## Use

Indoors in a dry room for hanging non-woven wallpaper.

On concrete, lightweight concrete, plaster, gypsum board, fibreglass, wood-fibre boards, veneer sheets, chipboard and sandblasted substrates.

## Substrate

Must be clean, dry, firm and suitable for substrate treatment.

## Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning.

Water-soluble discolouration, nicotine and soot are cleaned and treated with blocking primer.

Hard, smooth substrates should be sanded to a matt finish and painted with primer.

Cracks, unevenness and holes must be filled.

Paint absorbent and porous substrates with primer.

Untreated, painted and wallpapered substrates should be primed.

# Application

Apply on wall using brush, roller or spray gun with after rolling.  
Adjust layer thickness to substrate and wall covering.  
Apply uniformly wet on wet and finish by brushing/rolling in the same direction.  
Allow the adhesive to dry briefly before hanging the wallpaper.  
Differences in layer thickness or uneven structure can result in a non-uniform substrate.  
Insufficient layer thickness results in the risk of blistering and inadequate adhesion.  
Excess layer thickness results in the risk of cracking and visible stains.  
Adhesive applied to the front of the wallpaper may cause visible stains.  
Cold/heat can affect the viscosity of the material.  
Condensation must be prevented during drying/curing  
Cold and increased atmospheric humidity extends drying time and full curing.  
Increased temperature and low atmospheric humidity reduce drying time and full curing.  
Always perform a test treatment for a check and acceptance of adhesion and result.

## Expected result

Uniform and well fastened to substrate.  
Does not prevent penetration of knots and water-soluble dyes, water stains and nicotine.  
Exercise care in loading the substrate until the adhesive is fully cured.

## Please note!

Ensure good ventilation during and after hanging.

## Environmental information

Remove as much paint as possible from tools before cleaning. Bring remains of fluent paint to the local recycling centre.  
Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

**Storage:** Cool, frost free and tightly closed

## Technical Data

Product Type	[14]
Density (kgs/l)	1.06
Solids Weight %	22
Solids Vol. %	17
Nominal spreading rate (m <sup>2</sup> /ltr.)	5
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Dilution	Do not dilute
Cleaning of Tools etc.	Water

### Current TDS Version

June 2022

### Replaces TDS Version

May 2022

