

08 Wood Tex Sealer

Product properties

Water and dirt-repellent impregnation that provides long-lasting protection. This sealant minimises the risk of mould growth and the formation of cracks. Provides a diffusion-open treatment that protects against UV radiation. Used as a final treatment following pre-treatment with Wood Tex Patina.

- Environmentally friendly silicium technology
- Dirt and water-repellent
- Contains UV filter



Labelling



Product use

Pressure-impregnated fully exposed wood such as outdoor decks. The substrate must be treated with Flügger 08 Wood Tex Patina.

Substrate

Must be absorbent, clean, dry, solid and suitable for paint treatment. Insufficiently protected cross-cut wood, water traps or risk of water accumulation must not occur. The moisture level in the wood prior to paint treatment max. 20%.

Treatment

Loose wood stain, paint and decayed wood fibres must be removed by cleaning and sanding. Remove dirt, filth, grease and chalking material with Terrace Cleaner. Algae, mould and mould growth are removed by cleaning with Facade Anti-green. To be treated no earlier than 4 hours after treatment with Flügger 08 Wood Tex Patina.

Application

Brush.

Apply generously and let it work for about 15 minutes.

Distribute/spread excess liquid into the substrate.

Condensation must not form.

Avoid working in direct sunlight.

The surface must not be exposed to frost or rain for at least 24 hours after completing treatment.

Expected result

Colourless, water and dirt-repellent surface.

The appearance and durability of the surface depends on the wood quality, structure, application and exposure.

Cleaning and maintenance

Loose wood fibers are removed with a brush.

Dirt, grease and chalking material should be removed using Facade Clean.

Algae, mould and mould growth are removed by cleaning with Facade Anti-green.

Maintain with Flügger 08 Wood Tex Sealer every two years or as needed.

Please note!

Protect freshly painted surface from adverse weather conditions.

Take appropriate measures against the effects of moisture and rainfall on freshly painted surfaces.

The surface achieves maximum robustness when fully cured.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Impregnation
Density (kgs/l)	1.0
Nominal spreading rate (m ² /ltr.)	10
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Water

Current TDS Version

December 2024

Replaces TDS Version

October 2024

