

## 08 Wood Tex Sealer

Flügger Wood Tex is water-based products for exterior wood. They give the wood a highly weather-resistant surface with maximum durability, gloss and colour stability. The products are easy to apply and quick-drying.

### Product properties

Aqueous and dirt-repellent impregnation that provides long-lasting protection. This sealant minimises the risk of mould growth and the formation of cracks. Provides a diffusion-open treatment that protects against UV radiation. Used as a final treatment following pre-treatment with Wood Tex Patina.

- **Environmentally friendly silicium technology**
- **Dirt and water-repellent**
- **Contains UV filter**



### Product use

Pressure-impregnated wood such as terraces, balcony floors, eaves, gable cladding, facades, picket fences and garden furniture.

The substrate must be treated with Flügger 08 Wood Tex Patina.

### Substrate

Must be absorbent, clean, dry, solid and suitable for paint treatment.

Insufficiently protected cross-cut wood, water traps or risk of water accumulation must not occur.

The moisture level in the wood prior to paint treatment max. 20%.

### Treatment

Loose wood stain, paint and decayed wood fibres must be removed by cleaning and sanding.

Remove dirt, filth, grease and chalking material with Terrace Cleaner.

Algae, mould and mould growth are removed by cleaning with Facade Anti-green.

To be treated no earlier than 4 hours after treatment with Flügger 08 Wood Tex Patina.

### Application

Brush.

Apply generously and let it work for about 15 minutes.

Distribute/spread excess liquid into the substrate.

Condensation must not form.

Avoid working in direct sunlight.

The surface must not be exposed to frost or rain for at least 24 hours after completing treatment.

### Expected result

Colourless surface.

The durability of the surface depends on the wood quality, structure, application and exposure.

## Please note!

Protect freshly painted surface from adverse weather conditions.  
Take appropriate measures against the effects of moisture and rainfall on freshly painted surfaces.  
The surface achieves maximum robustness when fully cured.

## Environmental information

Clean off the paint from tools and wash them with water. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

**Storage:** Cool, frost free and tightly closed

## Technical Data

Product Type	Impregnation
Density (kgs/l)	1.0
Nominal spreading rate (m <sup>2</sup> /ltr.)	10
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Water

### Current TDS Version

November 2022

### Replaces TDS Version

May 2022