

# Natural Wood Boat Varnish

## Product properties

Specially formulated varnish for treatment on natural wood. Provides a robust, weather and saltwater resistant surface. Natural Wood Boat Varnish is available in semi-gloss or gloss.

- Specially for natural wood
- Robust surface
- Glossy or semi-gloss



## Labelling



## Product use

Used indoors and outdoors for varnishing natural wood.

## Substrate

Must be clean, dry, solid and suitable for surface treatment.

## Treatment

Uneven or loose varnish and paint are completely removed to clean wood by sanding. Remove dirt, grime, grease and chalking materials with Natural Wood Cleaner. Algae, mould and mildew growth is removed by cleaning with Facade Algae Remover. Sand previously varnished surfaces matt, avoid sanding through.

Wipe dry with a hard-wrung cloth.

Prime untreated wood with Flügger 01 Wood Tex Priming Oil.

Optimum durability and results are achieved with 3 treatments before use.

Always carry out a test treatment to verify and accept the adhesion and result.

## Application

Brush.

After priming, apply 3 coats of undiluted Natural Wood Boat Varnish.

Apply wet-on-wet, and finish by brushing in the same direction.

Condensation during drying / curing must not form.

Avoid working in direct sunlight.

Cold and increased humidity extends drying time, full curing and recoating interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

## Expected result

Saturated surface with uniform gloss and finish.

The durability of the surface depends on wood quality, construction, application and exposure.

## Cleaning and maintenance

Clean the surface and repair any damage once a year or as needed.  
Remove dirt, grime and any mild fouling with Facade Clean.

## Please note!

Protect freshly painted surface from adverse weather conditions.  
Take appropriate measures against the effects of moisture and rainfall on freshly varnished surfaces.  
The surface achieves maximum robustness when fully cured.

## Environmental information

Minimise paint waste by calculating in advance how much paint to use.  
Remove as much paint as possible from tools before cleaning.  
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.  
Empty and dry packaging should be sorted as metal.

## Storage

Cool, frost free and tightly closed

## Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.  
Avoid inhalation of spray mist and grinding dust.  
Wear suitable protective equipment, see safety data sheet for further information.

## Technical Data

Gloss	Gloss;Semi Gloss
Density (kgs/l)	0.90
Solids Weight %	46
Solids Vol. %	40
Nominal spreading rate (m <sup>2</sup> /ltr.)	8
Long spreading rate (m <sup>2</sup> /l.)	10
Short Spreading rate (m <sup>2</sup> /ltr.)	6
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	4
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	White spirit and brush cleaner
Country of Origin	Sweden

# Current TDS Version

December 2024

# Replaces TDS Version

April 2024