

Wet Room Primer

Flügger Wet Room Paint and Wet Room Primer are used for surface treatment in bathrooms and similar rooms. The products are used subject to applicable legislation and notices regarding requirements for substrate, performance and water and moisture density.



Properties

Transparent blue-toned wet room primer. Glue and primer for installation and primer treatment of glass tissue/glass felt. Recommended for surfaces that are exposed to particularly high functional requirements, where changing moisture and water conditions occur. Included in Flügger wet room treatment for Flügger Wet Room Paint finishing.

- Primer paint and glue
- Blue toned

Use

Bathrooms, toilets and similar wet rooms.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.
Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.
Remove lime and soap residue using Fluren 33.
Sand hard, slippery surfaces flat.
Fill cracks, holes and unevenness using Sandplast LW.
Absorbent and porous substrate primed with Sealer.
Install glass tissue/glass felt using Flügger Wet Room Primer.
Finish treatment after 24 hours with 2 coats of Flügger Wet Room Paint.

Application

Brush or roller.
Decide your choice of tool/utensil depending on the finish
Apply Flügger Wet Room Primer and install wall covering on the wet primer/glue.
After 5 minutes, apply another coat of wet room primer to the wall covering.
Apply wet on wet and finish by brushing/rolling in the same direction
Cold/heat can affect the viscosity of the material
Condensation during drying/curing must not occur.
Cold and increased humidity extends drying time, full curing and recoat interval
Increased temperature and low atmospheric humidity reduce drying time and full curing
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Transparent, blue-tinged surface.

Finish treatment with Flügger Wet Room Paint.

Coat the surface with care and avoid direct contact with water before the paint is fully cured.

Environmental information

Clean off the paint from tools and wash them with water. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost free and tightly closed

Supplementary Info

Registered in the Nordic Ecolabelling Building Products Database for products which can be used in buildings with the Swan label.

Technical Data

Product Type	Adhesive & Glue;Priming paint
Density (kgs/l)	1.04
Solids Weight %	47
Solids Vol. %	45
Nominal spreading rate (m ² /ltr.)	3
Long spreading rate (m ² /l)	3
Short Spreading rate (m ² /l)	1
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute/do not tint
Cleaning of Tools etc.	Water

Current TDS Version

August 2022

Replaces TDS Version

May 2022