

Wet Seal

Product properties

Elastic neutral-cure silicone sealant, indoors and outdoors. UV resistant with extra strong adhesion and elasticity. Prevents the formation of mould and mould growth.

- **Extra elastic**
- **Prevents the formation of mould and mould growth**
- **Extra strong adhesion**



Product use

Used for covering and sealing of joints in kitchens and bathrooms, and outdoors for sealing between building components.

Adheres to sanitary appliances, glass, ceramics, metal, PVC, glazed surfaces and primed, varnished or painted surfaces.

The sealant should be dimensioned so that the sealant's movement is below +/- 25%.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.

Prime new or bare, cleaned wood indoors with Interior Stop Primer.

Prime new or bare cleaned wood with Wood Tex 01 Priming Oil.

Absorbent and porous substrates can be primed with Fix Primer.

Use the correct size/amount of joint sealant, joint depth = ½ sealant width.

Narrow cracks and joints are best treated as square joints.

Application

Filler gun.

Cut off the tip of the filler gun.

Cut the tip at an angle to adjust to < joint width.

Easily workable, press into place and smooth using a sealer squeegee or joint stick and water before the joint forms a skin.

Choose a tool based on the width of the joint.

Remove excess sealant mechanically.

Apply sealing tape if necessary and remove it immediately after application.

Cold/heat can affect the viscosity of the material.

Avoid condensation formation.

Temperature and humidity affect drying time, curing and recoat intervals.

Always test for control and acceptance of adhesion and result.

Expected result

Extra elastic joints, which can absorb temperature- and moisture-related movements.
Cannot be sanded or painted.
Withstands moisture and water.
Risk of yellowing of the joint if used on alkyd paint which has not fully cured.

Please note!

Do not use for aquariums or on natural stone such as marble or granite.

Environmental information

Clean off the sealant from tools and wash them with white spirit. Bring remains of fluent sealant to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage

Cool, frost-free, and tightly closed

Supplementary Info

Shelf life: 12 months in unopened container.

Technical Data

Product Type	Plaster & Sealant
Density (kgs/l)	1.0
m/l, depending on joint width and depth	18
Min. working temp. during application and drying/curing	Min. +5°C
Heat Resistance Max. (°C)	Max. +180°C
Humidity	Max. humidity 80 % RH.
Fully cured at 20° C, 60 % RH (Days)	8
Joint Movement (%)	25
Hardness (Mohs)	16 ± 5 Shore A
Volume Shrinkage (%)	0
Cleaning of Tools etc.	Remove uncured sealant with white spirit. Remove hardened sealant mechanically.

Current TDS Version

October 2024

Replaces TDS Version

March 2024

